

Page 1/8

Safety data sheet according to 1907/2006/EC

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RETOUCHING VARNISH 004
- · Article number: 24285004, 24305004, 24325004
- · **UFI:** H610-U0V3-K001-XE4Q
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use: Picture varnish

· 1.3 Manufacturer/Supplier:

Manufacturer: Royal Talens P.O. Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

UK Distributor: R.Talens UK Ltd P.O. Box 3717 Wokingham RG40 9RS, UK Tel +44 (0)800 995 6500

· Further information obtainable from:

Regulatory Affairs safety@royaltalens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Birmingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

(Contd. of page 1)



STOT SE 3 H336 May cause drowsiness or dizziness.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02

GHS07

HS07 GH

HS08 GHS0

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9, aromatics

· Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to hazardous waste collection point.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:				
EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, $<2\%$ aromatics	30-50%		
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	25-30%		
Reg.nr.: 01-2119473851-33	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066			
	Hydrocarbons, C9, aromatics	5-10%		
EC/List number: 918-668-5 Reg.nr.: 01-2119455851-35	Flam. Liq. 3, H226; ♣ Asp. Tox. 1, H304; ♠ Aquatic Chronic 2, H411; ♠ STOT SE 3, H335-H336, EUH066			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

GB

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water spray
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases/vapours is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: -
- 7.3 Specific end use(s) No further relevant information available.

GE

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

	· 8.1 Control parameters					
	Ingredients with limit values that require monitoring at the workplace: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics (25-30%)					
Hydrocarl						
TWA Long	TWA Long-term value: 1000 mg/m³, 200 ppm					
· DNELs	DNELs					
Hydrocarl	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics					
Oral	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)				
Dermal	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)				
		208 mg/kg bw/day (Employee)				
Inhalative	DNEL,long term (chronic) - systemic effects	185 mg/m3 (Consumer)				
		871 mg/m3 (Employee)				
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Oral	DNEL,long term (chronic) - systemic effects	699 mg/kg bw/day (Consumer)				
Dermal	DNEL,long term (chronic) - systemic effects	699 mg/kg bw/day (Consumer)				
		773 mg/kg bw/day (Employee)				
Inhalative	DNEL,long term (chronic) - systemic effects	608 mg/m3 (Consumer)				
		2,035 mg/m3 (Employee)				
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics					
Oral	DNEL,long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)				
Dermal	DNEL,long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)				

- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment

Inhalative DNEL,long term (chronic) - systemic effects | 32 mg/m3 (Consumer)

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not necessary if room is well-ventilated.

Only during spraying without adequate removal by suction.

· Hand protection



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

25 mg/kg bw/day (Employee)

150 mg/m3 (Employee)

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Safety glasses if risk of splashes.

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

• Odour: Characteristic
• Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 107-137 °C • Flammability Highly flammable.

· Lower and upper explosion limit

 · Lower:
 0.7 Vol %

 · Upper:
 6.8 Vol %

 · Flash point:
 1 °C

 Net determine
 Net determine

• **Decomposition temperature:** Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity at 40 °C <20.5 mm²/s · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 2 hPa

Density and/or relative density

• **Density at 20 °C:** 0.81 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and

environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition · Softening point/range

• Oxidising properties No further relevant information available.

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water

Substances and mixtures, which emit flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

GB

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- · 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

- · 10.4 Conditions to avoid Keep away from sources of ignition No smoking.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification:				
Hydrocarb	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	>5,000 mg/l (rat)			
Hydrocarb	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
Inhalative	Inhalative LC50/4 h >20 mg/l (rat)				
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics				
Oral	LD50	2,000-5,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rabbit)			

- · **STOT-single exposure** May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Version: 1.2 (replaces version 1.1) Printing date 21.11.2022 Revision: 21.11.2022

Toxic for aquatic organisms

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	I 2 6 3 P A I N T R E L A T E D M A T E R I A I ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL
	TAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR	
Class	3 Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	None.
· ADR, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substance Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	Maximum nei quantity per outer packaging. 500 mt
Transport category Tunnel restriction code	D/E
	<u> </u>

Printing date 21.11.2022 Version: 1.2 (replaces version 1.1) Revision: 21.11.2022

	(Contd. of page 7)
· IMDG	
· Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
1 1	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II,
<u> </u>	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* * Data compared to the previous version altered.