

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878
Issue date: 21/10/2022 Revision date: 21/10/2022 Supersedes version of: 18/11/2021 Version: 8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH
UFI : QY5D-S2X0-C902-7CM3
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

COLART EUROPE SAS SAS
5 rue René Panhard 72021 Le Mans Cedex 2
72021 LeMans
France
T +44 208 424 3270
r.enquiries@colart.co.uk

Other

Colart International Holdings LTD
The MediaWorks Building
191 Wood Lane
GB- W12 7FP London – London
United Kingdom
T 02084243200
r.enquiries@colart.co.uk

Distributor

COLART UK LTD
Goldthorn Road
DY11 7JN Kidderminster – Worcestershire
United Kingdom
T +44 (0) 2084243200
r.enquiries@colart.co.uk

Manufacturer

Colart France
Zone Industrielle Nord 5 Rue René Panhard, +33 2 43 83 83 00
Le Mans
France
r.enquiries@colart.co.uk

Distributor

Jasco Pty (NZ) Limited
5 Airpark Drive, Airport Oaks, Auckland Airport Auckland
P.O. Box 107010

Distributor

JASCO
1-5 Commercial Road Kingsgrove
+61- NSW 2208 New South Wales
T 029807 1555

1.4. Emergency telephone number

Emergency number : +33 2 43 83 83 00 (Monday- Thursday: 8:00-12:00 13:30-16:00 , Friday: 8:00-12:00 CET Language French); (+44) 2084243200 Monday-Friday: 9:00-17:00 GMT Language English)

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145 Westmead	13 11 26	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
New Zealand	New Zealand National Poison Centre Dunedin School of Medicine, University of Otago	PO Box 56 Dunedin 9054	0800 764 766 (0800 POISON)	

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: STODDARD SOLVENT

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H372 - Causes damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. – No smoking.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P260 - Do not breathe dust, fume, gas, mist, spray, vapours.
P102 - Keep out of reach of children.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains Benzotriazol derivative, Terpinolene multiconstituent. May produce an allergic reaction.
EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening

: Applicable

Tactile warning

: Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
STODDARD SOLVENT	CAS-No.: 8052-41-3 EC-No.: 232-489-3	30 – 50	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
HYDROCARBONS, C10-C12, ISOALKANES, <2% AROMATICS	CAS-No.: 90622-57-4 EC-No.: 923-037-2	10 – 30	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Terpineol multiconstituent	CAS-No.: 8000-41-7 EC-No.: 232-268-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319
NONANE	CAS-No.: 111-84-2 EC-No.: 203-913-4	1 – 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
1,2,4-TRIMETHYLBENZENE	CAS-No.: 95-63-6 EC-No.: 202-436-9	1 – 3	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9	< 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Terpinolene multiconstituent	EC-No.: 938-945-4	0.1 – 1	Flam. Liq. 3, H226 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzotriazol derivative	CAS-No.: 104810-47-1 EC-No.: 400-830-7	0.1 – 1	Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from	: Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight.	

7.3. Specific end use(s)

Refer to section 1.2.1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Avoid contact with eyes. Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Nitrile-rubber protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

Work in a well-ventilated area. No respiratory protection needed under normal use conditions. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use. Ensure there is adequate ventilation.

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≈ 41 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 0.27255 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Acute toxicity (inhalation) : Not classified

Benzotriazol derivative (104810-47-1)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
---------------	--

LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
--------------------	--

Terpineol multiconstituent (8000-41-7)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

LC50 Inhalation - Rat	> 4.76 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
-----------------------	--

Terpinolene multiconstituent

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
---------------	---

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Terpineol multiconstituent (8000-41-7)

NOAEL (animal/male, F0/P)	250 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
---------------------------	---

NOAEL (animal/female, F0/P)	> 250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
-----------------------------	---

STOT-single exposure : Not classified

Toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

NONANE (111-84-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

1,2,4-TRIMETHYLBENZENE (95-63-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)

LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Toluene (108-88-3)	
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Terpineol multiconstituent (8000-41-7)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Terpinolene multiconstituent	
NOAEL (oral, rat, 90 days)	435.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STODDARD SOLVENT (8052-41-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH	
Viscosity, kinematic	> 20.5 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Benzotriazol derivative (104810-47-1)	
EC50 - Other aquatic organisms [1]	4 mg/l Test organisms (species): other aquatic crustacea:DM
EC50 72h - Algae [1]	> 9 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
Terpineol multiconstituent (8000-41-7)	
LC50 - Fish [1]	62 – 80 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	≈ 68 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	≈ 17 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Terpinolene multiconstituent	
LC50 - Fish [1]	6.104 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	5.184 mg/l Test organisms (species): Daphnia magna

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available





SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	PAINT RELATED MATERIAL
Transport document description			
UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E)	UN 1263 PAINT RELATED MATERIAL, 3, III	UN 1263 Paint related material, 3, III	UN 1263 PAINT RELATED MATERIAL, 3, III
14.3. Transport hazard class(es)			
3	3	3	3
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			



WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 0.27255 %

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : STODDARD SOLVENT, Terpeneol multiconstituent are listed

SZW-lijst van mutagene stoffen : STODDARD SOLVENT, Terpeneol multiconstituent are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Switzerland

Swiss National Regulations

- : Article 13 Order on the protection of maternity (RS 822.111.52):
Pregnant women and breastfeeding mothers cannot come into contact with this product (this substance/this preparation) when working except where it has been established, on the basis of a risk analysis performed in accordance with Art. 63 OLT 1 (RS 822.111), that there is no concrete threat to the health of the mother or baby or that said threat can be excluded thanks to the suitable protection measures taken.
- Article 4, subparagraph 4 Order on the protection of young workers (OLT 5, RS 822.115) and Article 1, letter f Order of the DEFR on dangerous works for young workers (822.115.2):
Young workers undergoing initial professional training cannot work with this product (this substance/this preparation) except where envisaged in the order of professional training to achieve the training purposes and if the training plan conditions and applicable age limits are respected. Young workers who do not undergo initial professional training cannot work with this product (this substance/this preparation). Workers of either sex aged under 18 years old are considered as young.

Storage class (LK)

CH - VOC (SR 814.018)

- : LK 3 - Flammable liquids
: 0.929629009876544 %

United Kingdom / Australia / New Zealand

Other information

- : This Safety Data Sheet is compliant to WHS and ADG requirements.
This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555
Police and Fire Brigade : 000
Poisons information centre : 13 11 26
Safety Data Sheet applicable regions : Australia

This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals. Supplied as permitted by New Zealand regulations; EPA Hazardous Substances (Safety Data Sheet) notice.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555
Poisons information centre : 0800 764 766 (0800 POISON)
Safety Data Sheet applicable regions : New Zealand.

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Benzotriazol derivative, Terpinolene multiconstituent. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3

WINSOR & NEWTON OIL COLOUR ARTISTS' SATIN VARNISH

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.